

GM651

LTE Mobile Radio

- Abundant services
- Loud and clear sound
- 5-inch qHD screen
- DMO
- IP54



Technical Specifications

Genera		
Technology		FDD-LTE; DMO
3,	LTF	FDD B3/B20/B31
	WCDMA	B1
Frequency	GSM	B2/B3/B5/B8
	DMO	400 ~ 470 MHz
	LTE	23 ± 2dBm
Maximum Tx power	WCDMA	23 dBm ± 2 dBm
ix power	DMO	30 dBm
Size ($W \times H \times D$)		180 mm × 100 mm × 70mm
Weight		About 1.2 kg
Screen		5.0" 960 × 540 QHD
Touch screen		Capacitive multi-point touch screen
Operating system		Android 4.1
CPU		Qualcomm quad - core 1.2 GHz processor
Memory		RAM: 1 GB; ROM: 8 GB
Camera		No built - in camera Supports an add - on USB camera or IP camera
		Power interface, 26 - pin data / audio interface, and high - speed
External interface		ethernet interface
Antenna interface		2 for LTE, 1 for WCDMA, 1 for DMO, and 1 for GPS / GLONASS
Bluetooth		BT2.1+EDR/4.0
WLAN		WIFI 802.11 b/g/n, 2.4G, Support WiFi hotspot
Network		100 Mbps wired network Ethernet sharing
Location		GPS, Glonass, BDS
	Audio recording	Format: AMR
	Audio playback	Format: MIDI, AMR, MP3, AAC+, QCP, WAV, and WMA
	Video playback	Format: MP4, H263, H264, and 3GP Maximum resolution: 720P with 50 frames per second
Extended memory		Micro SD, up to 32 GB
Power		Operating Voltage DC 13.6V \pm 15%
OTG		Supports connections with extensive accessories, for exampl UVC devices
Development interface		Serial port that supports secondary development
Enviro	nmental	
Operating temperature		- 20 °C ~ + 60 °C
Storage temperature		- 40 °C ~ + 85 °C
ESD		IEC 61000-4-2 (level4)±8kV (Contact)±15kV (Air)
Dust and Water Resistance		IP54
Reliability		MIL - STD 810 G

PTT Services (dependent on PTT client)

General Functions	
Video private call	•
Video group call	•
Video transmission	•
Voice private call	•
Voice group call	•
Broadcast call	•
Emergency call	•
DMO PTT	•
Call dispatch console	•
Temporary group call	•
Automatic group information update	•
Late entry/PTT floor queue/PTT floor status alter	•
Inter-fleet call	•
Dispatch based on GIS map	•
Stun and Revive	•

Standard Accessories









